

PRODUCT SPECIFICATIONS SHEET

Model: Jazzy Ultra Light

Document Information: INFINF B4670/Rev B/December 2024

Weight Capacity	300 lbs. (136 kg) 21 stone 6 lbs.
Class of Use ⁷	A
Maximum Speed ¹	Up to 3.69 mph (5.94 km/h)
Ground Clearance ²	2.17 in. (55 mm) at motor
Turning Radius ²	33.19 in. (843 mm)
Overall Size ^{2, 6}	Length: 40.91 in. (1039 mm) Width: 24.49 in. (622 mm)
Drive Wheels	10.71 in. (272 mm), Flat free
Caster Wheels	8 in. (203 mm), Flat free
Suspension	Suspension Caster Forks
Range ^{1, 4}	10Ah: Up to 8 miles (12.9 km) at 200 lbs. (90.72 kg) 14 stone 4 lbs. Up to 7 miles (11.3 km) at 300 lbs. (136.1 kg) 21 stone 6 lbs. 20Ah: Up to 16.4 miles (26.3 km) at 200 lbs. (90.72 kg) 14 stone 4 lbs. Up to 14.4 miles (23.1 km) at 300 lbs. (136.1 kg) 21 stone 6 lbs.
Component Weights ⁵	Complete Assembly (without battery box, cushion, and cupholder): 32.6 lbs. (14.8 kg) 10Ah Battery Box: 4.96 lbs. (2.25 kg) 20Ah Battery Box: 7.4 lbs. (3.4 kg)
Seat Dimension ²	Width: 18 in. (457 mm) Depth: 18 in. (457 mm)
Drivetrain	Two motor, rear-wheel drive
Brakes	"Intelligent Braking" electronic regenerative, disc park brake
Batteries ³	10Ah, 25.2V Lithium-ion 20Ah, 25.2V Lithium-ion
Battery Charger	Off-board
Freewheel Operational Force	Less than 60 N
Drive Control Operational Force	Less than 5 N
Maximum Rated Slope	6° (10.5%)
Maximum Obstacle Climbing Ability (Ascending and Descending)	0.98 in. (25 mm)
Measured Sound Level (A-weighted)	Less than 65 dB

¹ Varies with base model, user weight, terrain type, battery amp hour rating (Ah), battery charge, battery condition, motors, controller type, tire type, and tire condition. This specification is subject to a variance of +10%, -5%.

² Due to manufacturing tolerances and continued product improvement, this specification can be subject to a variance of (+ or -) 3%.

³ AGM, Gel-Cell, Lithium-Ion, or Hybrid Gel (Hybrid Gel is defined as Nano Silica Gel Electrolyte with High Quality Glass Mat Separators) type required. See III. "Batteries and Charging."

⁴ Tested in accordance with ANSI/RESNA, WC Vol. 2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.

⁵ Battery weight may vary based on manufacturer.

⁶ Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

⁷ Class A achieved with 20Ah batteries.

**NOTE: This product conforms to all applicable ANSI/RESNA and ISO 7176 Series standards.
All specifications subject to change without notice.**



ACN 088 609 661



I N F I N F B 4 6 7 0

